

## **RESETTABLE DISPLAY**

The ME6-T is a remote display for water meters. It features a dual line display with flowrate and totaliser. The LCD has 6 digits and can be programmed for litres or kilolitres with adjustable decimal point. These units will be factory programmed to your meter specifications.

Great for manual batching. Just close the lid to reset the totaliser to zero.

- 10 Year + Battery Life
- ASA Enclosure. UV Resistant
- Dual Line LCD with Flow Rate
- Flow Indicator
- Resettable
- IP65 Rated

## LCD Display



- Litres, Kilolitres
- Flow rate L/M, L/S

Accuracy	Dependent on flowmeter connected (refer equipment specifications) Digital input.
Display Readout	Counter: 6 Digit LCD. Litres or Kilolitres with decimal places
Programming	Option 1: via 3 internal push buttons Option 2: via PC with RFID reader and EWM Calibration software or ANDROID device with built-in NFC and EWM application
Power Source	3.6v replaceable lithium battery (typically in excess of 10 year life)
Display Housing Ingress	IP65
Max. Ambient Temperature	55 °C
Pulse input (compatibility)	All square waveforms and Voltage free switching (500hz max.)
Pulse Output (optional)	N-Channel MOSFET, 5-100VDC 1 Amps, 100 Hz maximum
External Reset Input (option)	Passive input via 2 wire volt free contact for PLC or external totaliser reset switch.
Dimensions:	52mm (H) x 84mm (W) x 84mm (L) Fastening lugs with 94mm centers
Weight (unpacked)	0.4 kg

## flotech.com.au | (02) 4572 0974 | sales@flotech.com.au





## Flotech.com.au